


California High-Speed Rail Authority

Los Angeles to San Diego via the Inland Empire Section

High-Speed Train Project

Open House Meetings 2011




California High-Speed Rail Authority

Los Angeles to San Diego via the Inland Empire Section

High-Speed Train Project

Open House Meetings 2011



S1 - LA Union Station to Ontario Airport

Los Angeles to San Diego
via the Inland Empire Section


Subsection 1
Los Angeles Union Station to Ontario International Airport

California High-Speed Rail Authority

Los Angeles to San Diego via the Inland Empire Section

High-Speed Train Project

Open House Meetings 2011




California High-Speed Rail Authority

Los Angeles to San Diego via the Inland Empire Section

High-Speed Train Project


Open House Meetings 2011




Commitment to Sound Mitigation

Engineering and design will make a big difference

- Sound engineers and train builders have over 40 years experience – and good mitigation measures are working around the world.
- For a train traveling less than 160 mph, a six to 12-foot sound barrier will **reduce noise by five to nine decibels** (the human ear perceives a 10-decibel reduction as cutting the sound in half).
- The sound from a high-speed train operating on an aerial structure could be **one or two decibels higher** than at ground level.
- The sound from a high-speed train operating in an open trench could be **five to seven decibels lower** than at ground level.



Noise levels without sound barrier



Noise levels with sound barrier